SAFETY DATA SHEET Prime Hybrid Oil for Decks and Garden Furniture

Commission Regulation (EU) No 2015/830 of 28 May 2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Prime Hybrid Oil for Decks and Garden Furniture

1.2. Relevant identified uses of the substance or mixture and uses advised

<u>against</u> Identified uses Decorative effect coatings.

Uses advised againstNo specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Hemel Boya ve Kimya Sanayi A.Ş.

Adres: I.D.O.S.B. Vakum Cd. No:25 B-1 Özel

Parsel Tuzla/Istanbul/Turkey

Tel: +90 444 98 48 Fax: +90 (216) 394 83 10 hakan.milli@hemel.com.tr

1.4. Emergency telephone number

Emergency telephone HEMEL: +90 444 98 48

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Hazard statements EUH208 Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol, 3-iodo-2-propynyl butylcarbamate,

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-

2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P273 Avoid release to the environment.

P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

1,2-Propylene glycol

CAS number: 57-55-6 EC number: 200-338-0

Classification
Not Classified

Prime Hybrid Oil for Decks and Garden Furniture

Ethanol 1-2%

CAS number: 64-17-5 EC number: 200-578-6

Classification

Flam. Liq. 2 - H225

(2-methoxymethylethoxy)propanol

Classification

Not Classified

Amines, tallow alkyl, ethoxylated <1%

CAS number: 61791-26-2 M factor (Chronic) = 1

Classification

Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 1 - H410

2-butoxyethanol <1%

CAS number: 111-76-2 EC number: 203-905-0

Classification

Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319

2,4,7,9-tetramethyldec-5-yne-4,7-diol

CAS number: 126-86-3 EC number: 204-809-1

Classification

Eye Dam. 1 - H318 Skin Sens. 1B - H317 Aquatic Chronic 3 - H412

Prime Hybrid Oil for Decks and Garden Furniture

3-iodo-2-propynyl butylcarbamate <1%

Classification

Acute Tox. 4 - H302 Acute Tox. 3 - H331 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT RE 1 - H372 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

propan-2-ol (Isopropyl alcohol) <1%

CAS number: 67-63-0 EC number: 200-661-7

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

Kaolin <1%

Classification

Not Classified

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-2H -isothiazol-3-one [EC no.

220-239-6] (3:1)

CAS number: 55965-84-9

M factor (Acute) = 100 M factor (Chronic) = 100

Specific Concentration Limits - CMIT/MIT: Skin Corr. 1B; H314: $C \ge 0.6$ %, Skin Irrit. 2; H315: 0.06 % $\le C < 0.6$ %, Eye Irrit.

<1%

2; H319: 0,06 % \leq C < 0,6 %, Skin Sens. 1; H317: C \geq 0,0015 %

Classification

Acute Tox. 3 - H301

Acute Tox. 2 - H310

Acute Tox. 2 - H330

Skin Corr. 1C - H314

Eye Dam. 1 - H318

Skin Sens. 1A - H317

Aquatic Acute 1 - H400

Aquatic Chronic 1 - H410

The full text for all hazard statements is displayed in Section 16.

Composition comments See section 8 for workplace exposure limits.

Prime Hybrid Oil for Decks and Garden Furniture

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

> keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on

their side in the recovery position and ensure breathing can take place.

Ingestion Rinse mouth thoroughly with water. Remove any dentures. Stop if the affected person feels

> sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take

place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.

Skin contact After contact with skin, take off immediately all contaminated clothing, and wash immediately

with plenty of water. Get medical attention if any discomfort continues.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 10 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards. The severity of the symptoms

described will vary dependent on the concentration and the length of exposure.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may Ingestion

be inhaled, resulting in the same symptoms as inhalation.

Skin contact Prolonged contact may cause dryness of the skin.

Eye contact May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with foam, carbon dioxide, dry powder or water fog.

Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Thermal decomposition or combustion products may include the following substances:

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion

products Harmful gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material.

6.2. Environmental precautions

Environmental precautions

Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and

place it in a suitable waste disposal container.

Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment.

Prime Hybrid Oil for Decks and Garden Furniture

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store away from incompatible materials (see Section 10). Store in accordance with local

regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor

should be leak-tight, jointless and not absorbent.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

1,2-Propylene glycol

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ particulate

Long-term exposure limit (8-hour TWA): WEL 150 ppm 474 mg/m³ total vapour and particulates

Ethanol

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

(2-methoxymethylethoxy)propanol

Long-term exposure limit (8-hour TWA): 308 mg/m³ 50 ppm

2-butoxyethanol

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m³ Short-term exposure limit (15-minute): WEL 50 ppm 246 mg/m³

Sk

propan-2-ol (Isopropyl alcohol)

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³ Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

Kaolin

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³ inhalable fraction

Long-term exposure limit (8-hour TWA): 15 mg/m³ Total dust

WEL = Workplace Exposure Limit Sk = Can be absorbed through the skin.

Ethanol (CAS: 64-17-5)

DNEL Workers - Inhalation; : 1900 mg/m³

Workers - Dermal; Long term systemic effects: 343 mg/kg/day Workers - Inhalation; Long term systemic effects: 950 mg/m³

General population - Inhalation; : 950 mg/m³

General population - Dermal; Long term systemic effects: 206 mg/kg/day General population - Inhalation; Long term systemic effects: 114 mg/m³ General population - Oral; Long term systemic effects: 87 mg/kg/day

PNEC - Fresh water; 0,96 mg/l

marine water; 0,79 mg/l
Intermittent release; 2,75 mg/l
Sediment (Freshwater); 3,6 mg/kg
Sediment (Marinewater); 2,9 mg/kg

2-butoxyethanol (CAS: 111-76-2)

DNEL Consumer - Oral; Long term systemic effects: 3,2 mg/kg

Consumer - Inhalation; Long term systemic effects: 49 mg/m³ Consumer - Dermal; Long term systemic effects: 38 mg/kg Workers - Inhalation; Long term systemic effects: 98 mg/m³ Workers - Dermal; Long term systemic effects: 75 mg/kg

PNEC - Fresh water; 88 mg/l

marine water; 88 mg/lSediment (Freshwater): 34

Sediment (Freshwater); 34,6 mg/kgSediment (Marinewater); 3,46 mg/kg

Intermittent release; 91 mg/lSTP; 463 mg/l

propan-2-ol (Isopropyl alcohol) (CAS: 67-63-0)

DNEL Workers - Dermal; Long term systemic effects: 888 mg/kg/day

Workers - Inhalation; Long term systemic effects: 500 mg/m³

General population - Oral; Long term systemic effects: 26 mg/kg/day General population - Dermal; Long term systemic effects: 319 mg/kg/day General population - Inhalation; Long term systemic effects: 89 mg/m³

PNEC Fresh water; 140.9 mg/l

marine water; 140.9 mg/l

Sediment (Marinewater); 552 mg/kg Sediment (Freshwater); 552 mg/kg

Soil; 28 mg/kg STP; 2251 mg/l

Intermittent release; 140,9 mg/l

Oral; 160 g/kg

8.2. Exposure controls

Protective equipment







Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body

protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour No information available.

Odour Characteristic.

pH No information available.
 Melting point No information available.
 Initial boiling point and range No information available.

Flash point >60°C

Flammability (solid, gas)

No information available.

Upper/lower flammability or

No information available.

evalesive limite

explosive limits

Vapour pressure

No information available.

Vapour density

No information available.

No information available.

Viscosity

(DIN4,20°C): 12" ± 2

Explosive properties No information available.

Prime Hybrid Oil for Decks and Garden Furniture

Oxidising properties No information available.

9.2. Other information

Other information No information required.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity See the other subsections of this section for further details.

10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

312.5

ATE inhalation (dusts/mists

mg/l)

Skin corrosion/irritation

Skin corrosion/irritationBased on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Prime Hybrid Oil for Decks and Garden Furniture

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity

Based on available data the classification criteria are not met.

IARC carcinogenicity

Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable

as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

Based on available data the classification criteria are not met.

development

Specific target organ toxicity - single exposure

STOT - single exposureNot classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may

be inhaled, resulting in the same symptoms as inhalation.

Skin contact Prolonged contact may cause dryness of the skin.

Eye contact May cause temporary eye irritation.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target organs No specific target organs known.

Toxicological information on ingredients.

Ethanol

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 6200 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ 7060 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation

(LC₅₀ dust/mist mg/l)

30,000.0

Notes (inhalation LC₅o) LC50 124,7 mg/l, Inhalation, Rat

ATE inhalation 30,000.0

(dusts/mists mg/l)

Prime Hybrid Oil for Decks and Garden Furniture

Amines, tallow alkyl, ethoxylated

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

1,315.0

Species Rat

ATE oral (mg/kg) 1,315.0

2-butoxyethanol

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

1,414.0

Species Rat

Notes (oral LD₅₀) 615 mg/kg, Oral, Rat

ATE oral (mg/kg) 1,414.0

Acute toxicity - dermal

Notes (dermal LD₅₀) 405 mg/kg, Dermal, Rabbit

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀) 2,2 mg/l, Inhalation, Rat

ATE inhalation (vapours

mg/l)

11.0

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

3-iodo-2-propynyl butylcarbamate

Acute toxicity - oral

ATE oral (mg/kg) 500.0

Acute toxicity - inhalation

ATE inhalation

(dusts/mists mg/l)

propan-2-ol (Isopropyl alcohol)

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 5280 mg/kg, Oral, Rat

0.5

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ 12800 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Notes (inhalation LC50) LC50 72.6 mg/l, Inhalation, Rat

Carcinogenicity

IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Prime Hybrid Oil for Decks and Garden Furniture

ammonia, anhydrous

Acute toxicity - inhalation

ATE inhalation (gases

700.0

ppm)

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)

Acute toxicity - oral

100.0 ATE oral (mg/kg)

Acute toxicity - dermal

50.0 ATE dermal (mg/kg)

Acute toxicity - inhalation

ATE inhalation (vapours 0.5

mg/l)

SECTION 12: Ecological information

12.1. Toxicity

Toxicity Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

Ecological information on ingredients.

Ethanol

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 24 hours: 11200 mg/l, Oncorhynchus mykiss (Rainbow trout)

LC₅₀, 96 hour: 13.000 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 5012 mg/l, Ceriodaphnia dubia EC₅₀, 48 hour: 9.300 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅₀, 72 hours: 275 mg/l, Chlorella pyrenoidosa

EC₅₀, 72 hour: 5.000 mg/l, Algae

Acute toxicity -

microorganisms

EC₅₀, 4 hours: 5,8 g/l, Paramaecium caudatum

Acute toxicity - terrestrial LC₅₀, 48 hours: 0,1-1 mg/cm², Eisenia Fetida (Earthworm)

Amines, tallow alkyl, ethoxylated

Chronic aquatic toxicity

M factor (Chronic)

2-butoxyethanol

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hour: 1474 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hour: 1550 mg/l, Daphnia magna

Acute toxicity - aquatic EC₅₀, 72 hour: 911 mg/l, Pseudokirchneriella subcapitata

plants

Prime Hybrid Oil for Decks and Garden Furniture

3-iodo-2-propynyl butylcarbamate

Acute aquatic toxicity

LE(C)₅₀ $0.01 < L(E)C50 \le 0.1$

M factor (Acute) 10

Acute toxicity - fish LC₅₀, 96 hour: 0.43 mg/l, Brachydanio rerio (Zebra Fish)

LC₀, 96 hour: 0.26 mg/l, Brachydanio rerio (Zebra Fish)

Acute toxicity - aquatic

invertebrates

CE50, 48 hour: 0.21 mg/l, Daphnia magna CE0, 48 hour: 0.11 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

CE50, 72 hour: 0.01 mg/l, Scenedesmus subspicatus

CE0, 72 hour: 0.026 mg/l, Scenedesmus subspicatus

Chronic aquatic toxicity

M factor (Chronic) 1

propan-2-ol (Isopropyl alcohol)

Acute aquatic toxicity

Acute toxicity - fish LC₅o, 96 hours: 11130 mg/l, Pimephales promelas (Fat-head Minnow)

LC₅₀, 96 hours: 9640 mg/l, Pimephales promelas (Fat-head Minnow) LC₅₀, 96 hours: > 1400000 ug/L, Lepomis macrochirus (Bluegill)

LC₅₀, 96 hour: 4.200 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 13299 mg/l, Daphnia magna

EC₅o, 72 hour: 1000 mg/l, Scenedesmus subspicatus

Acute toxicity - aquatic

plants

IC₅₀, 72 hours: >1000 mg/l, Desmodesmus subspicatus

IC₅₀, 96 hour: 1.000 mg/l, Algae

Acute toxicity -

microorganisms

EC10, 16 hour: 5.175 mg/l, Bacteria

ammonia, anhydrous

Acute aquatic toxicity

LE(C)₅₀ $0.1 < L(E)C50 \le 1$

M factor (Acute)

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-2H -isothiazol-3-one

[EC no. 220-239-6] (3:1)

Acute aquatic toxicity

LE(C)₅₀ $0.001 < L(E)C50 \le 0.01$

M factor (Acute) 100

Acute toxicity - fish LC₅₀, 96 hour: 0.22 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hour: 0.12 mg/l, Daphnia magna

Chronic aquatic toxicity

M factor (Chronic) 100

Prime Hybrid Oil for Decks and Garden Furniture

NOEC-Aquatic Invertebrates

0.035 mg/l (Daphnia sp.)

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

Ethanol

Persistence and degradability

The substance is readily biodegradable.

propan-2-ol (Isopropyl alcohol)

Biodegradation - 78 %: 28 day

Biological oxygen demand 1,19 g O₂/g substance

Chemical oxygen demand 2,23 g O₂/g substance

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Ecological information on ingredients.

Ethanol

Partition coefficient log Kow: -0,31

(2-methoxymethylethoxy)propanol

Partition coefficient log Pow: 0.004 Low potential.

propan-2-ol (Isopropyl alcohol)

Partition coefficient log Pow: 0.05

Bioconcentration factor

(BCF)

. 3

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

12.6. Other adverse effects

Other adverse effects None known.

Prime Hybrid Oil for Decks and Garden Furniture

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods

Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EH40/2005 Workplace exposure limits.

Prime Hybrid Oil for Decks and Garden Furniture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

IATA: International Air Transport Association.

ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate.

LC₅o: Lethal Concentration to 50 % of a test population.

LD₅o: Lethal Dose to 50% of a test population (Median Lethal Dose).

EC₅o: 50% of maximal Effective Concentration.

PBT: Persistent, Bioaccumulative and Toxic substance.

vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations

and acronyms

Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Key literature references and

sources for data

This SDS is prepared based on the information received from the product owner.

Source: European Chemicals Agency, http://echa.europa.eu/

Classification procedures according to Regulation (EC)

1272/2008

Aquatic Chronic 3 - H412: : Calculation method.

Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this

material.

Revision commentsThis is the first issue.

Issued by Hakan MILLI

Certificate number: KDU01.13.06 Certificate Supersedes date: 22.02.2025

hakan.milli@hemel.com.tr

Revision date 30/01/2023

Revision 1.0

Supersedes date 30/01/2023

Hazard statements in full H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed. H302 Harmful if swallowed. H310 Fatal in contact with skin. H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H330 Fatal if inhaled. H331 Toxic if inhaled. H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs (Larynx) through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH208 Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol, 3-iodo-2-propynyl butylcarbamate, Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable