

HEMEL® Paint Stripper

Description: High-performance gel paint stripper for both exterior and interior use

General Features:

- Strips paint in one step
- Suitable for water-based and solvent-based paints
- Does not contain any harmful compounds like toluene, NMP, caustic, acids, and heavy odor
- Applied by brush, roller or airless spray gun
- Environmentally friendly

Packaging Size: 0,750 L., 2,5 L., 15 L. (Upon request)

Where to Use:

- Wood
- Metals including light metals and copper
- Concrete, natural stone, and other mineral surfaces

Product Data:

Viscosity (Brookfield, 20°C):	2400 cP
Density (g/cm ³):	1,08 ± 0,02
VOC (g/L):	250
Application Method:	Brush, roller or airless spray gun
Shelf Life (5-35°C):	2 years for unopened can
Number of Coats:	1 coat (may increase depending on paint thickness)
Consumption (m ² /L):	1-3 m ² (depending on the type of surface and application method)
Reaction Time (at 20°C and 40-65% relative humidity):	30 minutes-5 hours (depending on the paint type and thickness)
Thinning:	Ready to use, does not require thinning.

Surface Preparation:

- Test the product on a small area of the surface to be used before paint stripping.

Application:

- The product is ready to use and does not require thinning.
- Stir the product thoroughly before use.
- For brush application, use a flat brush with natural bristles. Artificial fiber brushes may react with the product.
- For airless spray gun application, apply the product with 0,21"-0,31" nozzle by a spraying angle of 40-50°.
- Applied layer thickness of the product should be thicker than the paint layer to be removed.

- As a common application method, apply the product in afternoon and wait until the next morning. Thus, the paint is completely dissolved and easily removed from the surface by a scraper.
- The reaction time is 30 minutes-5 hours depending on the type of the paint and the layer thickness.
- Before stripping paint, make sure the product interacts with the paint. Sometimes it may be necessary to apply several coats.
- Intense sunlight and strong winds can dry out the paint stripper fast. In those cases, product should be reapplied to the areas that have dried out.
- Dissolved paint can be removed with a scraper or a brush.

Instructions:

- Keep product closed when not in use.
- The product can also be used at temperatures below 0°C.
- The product should be stored at temperatures between 5°C to 35°C.
- Painting tools should be cleaned with plenty of warm water.

Safety Precautions:

- USE WITH ADEQUATE VENTILATION.
- KEEP OUT OF REACH OF CHILDREN.
- Do not transfer contents to other containers for storage.
- Do not use empty cans for other purposes.
- Avoid contact with eyes and skin.
- Wash hands after using.
- FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.
- Dispose of contents/cans in accordance with national regulations.
- Please refer to the Safety Data Sheet (SDS) of the product for health and safety information.