

Hemel® PRO SC 7730

Description: Industrial water-based exterior wood varnish for spray gun

Color: Clear

Gloss: Semi-gloss

Type: Water-based

General Features:

- Transparent
- Water repellent
- Allows wood to breathe
- UV resistant
- Thixotropic (can be applied vertically)
- Does not crack, peel or blister
- Lead-free
- Ready to use

Packaging Size: 15 L.

Where to Use:

- Suitable for all exterior wood except floors
- Doors and window joinery
- Shutters
- Claddings
- Fences
- Pergolas
- Balcony railings
- Roof fringes

Product Data:

| | |
|---|--|
| Solid Content (% weight): | 37,07 ± 1 |
| Viscosity (DIN4, 20°C): | 55" ± 2 |
| Density (g/cm³): | 1,03 ± 0,02 |
| VOC (g/L): | 39 |
| Application Method: | Spray gun or airmix |
| Shelf Life (5-35°C): | 2 years for unopened can |
| Number of Coats: | 2 coats |
| Coverage (m²/L): | 3-4 m² with 2 coats depending on wood type |
| Drying Time (at 20°C and 40-65% relative humidity): | Touch Dry: 30 minutes Recoat: 1,5-2 hours Complete Dry: 24 hours |
| Thinning: | Ready to use, does not require thinning |

Surface Preparation:

- Before applying the product, wait 4-6 hours for Hemel Pro SA 11XX applied surface to dry.

Application:

- The product is ready to use and does not require thinning.
- Stir the product thoroughly before use and check its homogeneity. Repeat this process during the application.
- Apply the product in 2 coats by spray gun (2,5-3 mm nozzle, min. 3 atm pressure) or airmix on Hemel Pro SA 11XX applied surface without sanding (wet on wet) and wait 1,5-2 hours between coats.
- For any reason, if 3 hours exceeded between coats, wait 24 hours and sand the surface with #220/240 sandpaper before applying the second coat.
- For the best result, slight sanding between coats is advised.

Maintenance (when the same product had been used before):

- Do not apply the product directly on pre-coated surfaces.
- Clean the wood surface completely from dirt and oil and perform a slight sanding.
- Thoroughly clean the generated dust.
- Repeat same process as described in "Application" with 1 or 2 coats depending on weathering.
- Inspect annually and maintain as required.

Instructions:

- FOR EXTERIOR USE ONLY.
- NOT SUITABLE FOR FLOORINGS.
- To achieve UV protection, the product, must be applied on Hemel Pro SA 11XX.
- Keep product closed when not in use.
- The general application temperature of the product is between 15°C to 25°C at a relative humidity range of 40-65%.

- The moisture content of the wood should be max. 20%.
- Do not apply the product under direct sunlight or rain.
- Do not apply linseed oil, basecoat/primer, yacht varnish before or after Hemel Pro SC 7730 applied surfaces.
- Wait 72 hours before packaging coated/finished goods.
- The product should be protected from freezing and stored at temperatures between 5°C to 35°C.
- Painting tools should be cleaned with soap and plenty of warm water after application.

Safety Precautions:

- USE WITH ADEQUATE VENTILATION.
- KEEP OUT OF REACH OF CHILDREN.
- Do not transfer contents to other containers for storage.
- Do not use empty plastic cans for other purposes.
- To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying.
- Avoid contact with eyes and skin.
- Wash hands after using.
- FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.
- Dispose of contents/plastic cans in accordance with national regulations.
- Please refer to the Safety Data Sheet (SDS) of the product for health and safety information.