

HEMEL® Rapid Oil

Description: Universal quick-drying and UV-resistant matt oil for all wood surfaces

Color: Black, Brown, Coffee, Gray, Maple, Smoked Oak, Teak, Walnut, White

Gloss: Matt

Type: Oil-based

General Features:

- Preserves and revitalizes the natural beauty of wood
- Abrasion and scratch resistant
- UV resistant
- Reduces splinter formation
- Easy maintenance
- Water repellent
- Child safe (EN 71-3 Certified)
- Ready to use

Packaging: 2,5 L., 15 L.

Where to Use:

- All exterior wooden surfaces, including decks
- All interior solid and veneered wooden surfaces
- Wooden floors
- Solid or veneered tables, chairs, kitchen benches and furniture

Product Data:

Solid content % (weight):	43 ± 1
Viscosity (DIN4, 20°C):	24" ± 2
Density (g/cm ³):	0,86 ± 0,02
VOC (g/L):	564
Application Method:	Brush, Cloth or roller
Shelf Life (5-35°C):	Two years for unopened can
Number of Coats:	Interior and exterior wooden surfaces: 2 coats Exterior decks: 1 coat
Coverage (m ² /L):	8-10 m ² (depending on wood type and application method)
Drying Time (at 20°C and 40-65% relative humidity):	Touch Dry: 6 hours Complete Dry: 16 hours
Thinning:	Ready to use, does not require thinning.

Surface Preparation (Exterior):

- Remove any dirt, oil, and wood dust from the surface.
 - **New Wood Surfaces:**
 - Sand the surface with sandpaper #80/120.
 - Thoroughly clean the generated dust
 - **Old Uncoated Wood Surfaces:**
 - Sand the weathered surface with sandpaper #80/120 or HEMEL Deck Restorer
 - Thoroughly clean the generated dust
 - **Coated/Varnished Wood Surfaces:**
 - Do not apply the product directly on pre-coated surfaces.
 - Remove the old paint/varnish from the surface thoroughly with sandpaper.
 - Thoroughly clean the generated dust

Surface Preparation (Interior):

- Do not use cellulose, polyurethane filler, or primer before applying the product. As a filler, mix the wood dust with the product and fill all gaps and joints of the parquet. Clean the excess paste after it has dried out.
 - **New Wood Surfaces:**
 - Clean the surface thoroughly.
 - Sand the surface with a parquet sanding machine or hand using sandpaper #120/150.
 - Thoroughly clean the generated dust and remove it from the surface with a vacuum cleaner.
 - **Pre-oiled Wood Surfaces:**
 - Clean the surface with a damp cloth to remove all dust and wait until it dries.
 - **Old Unpainted/Unvarnished Wood Surfaces:**
 - Sand the weathered/discolored surface for the desired finish. It is recommended to sand with sandpaper #120 for a natural texture and #180-220 for a smoother texture.
 - Thoroughly clean the generated dust and remove it from the surface with a vacuum cleaner.
 - **Varnished Wooden Surfaces:**
 - Do not apply the product directly on pre-coated surfaces.
 - Remove the old varnish from the parquet completely with a scraping machine.
 - Remove any dirt, oil, wood dust, and old varnish residues from the surface.
 - Sand the surface to the desired finish. It is recommended to sand with sandpaper #120 for a natural texture and #180-220 for a smoother texture.
 - Thoroughly clean the generated dust and remove it entirely from the surface with a vacuum cleaner.
 - Remove the remaining dust with a damp cloth

Application:

- The product is ready to use and does not require thinning.
- Stir the product thoroughly before use and check its homogeneity. Repeat this process during the application.
- For best results on interior and exterior wood, apply two coats with a roller or brush, and brush off excess oil.
- For best results on exterior wooden decks, apply one coat with a roller or brush, and brush off excess oil.
- Apply in the direction of the wood grain to get a homogeneous look
- The treated surfaces can be stepped on after 24 hours

Maintenance (when the exact product had been used before):

- Do not apply the product directly on pre-coated surfaces.
- Clean the wood surface entirely from dirt and oil and perform a slight sanding.
- Thoroughly clean the generated dust.
- Repeat the same process as described in "Application."
- Inspect annually and maintain as required.

Instructions:

- FOR INTERIOR AND EXTERIOR USE.
- Never use any cellulosic, polyurethane, etc. filler or primer before applying HEMEL Rapid Oil.
- Keep product closed when not in use.
- The general application temperature of the product is between 15°C to 25°C at a relative humidity range of 40-65%.
- The moisture content of the wood should be max. 20%.
- Do not apply the product under direct sunlight or rain. The area should be ventilated during and after the application to promote drying.
- Oiled interior floors should not be cleaned with ammonia-containing cleaning materials.
- The treated surfaces can be stepped on after 24 hours. Allow seven days before spreading the carpet and cleaning.
- The product should be stored at temperatures between 5°C to 35°C.
- Painting tools should be cleaned with mineral spirits after the application

Safety Precautions:

- USE WITH ADEQUATE VENTILATION.
- KEEP OUT OF REACH OF CHILDREN.
- Do not transfer contents to other containers for storage.
- Do not use empty cans for other purposes.
- To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying.
- Avoid contact with eyes and skin.
- Wash hands after using.
- FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. Call Poison Control Center, hospital emergency room, or physician if swallowed.
- Dispose of contents/cans by national regulations.

- Please refer to the product's Safety Data Sheet (SDS) for health and safety information.

Certificates:

- EN71-3 Oyuncak Güvenliđi Sertifikası