



Prime Deck Oil

Description: Water-based hybrid oil for decks and garden furniture

Color: Walnut, Natural, Teak, Light Oak, Light Walnut, Pine, Mustard

Type: Water-based

General Features:

- Translucent tinted oil
- Does not cause darkening on ThermoWood®
- Preserves the natural appearance of wood
- Deep rich tones that highlight the wood grain
- Applied by brush, cloth, roller or dipping
- Odorless
- Child safe (EN 71-3 Certified)
- Ready to use

Packaging Size: 2,5 L., 15 L.

Where to Use:

- Fences
- Decks
- Garden furniture
- Pergolas
- Balcony railings

Product Data:

Solid Content % (weight):	17,9 ± 2
Viscosity (DIN4, 20°C):	12'' ± 2
Density (g/cm ³):	1 ± 0,03
VOC (g/L):	73
Application Method:	Brush, cloth, roller or dipping
Shelf Life (5-35°C):	2 years for unopened can
Number of Coats:	1 coat or 2 coats
Coverage (m ² /L):	10-12 m ² with 1 coat depending on wood type
Drying Time (at 20°C and 40-65% relative humidity):	Recoat: 4-6 hours Complete Dry: 16 hours
Thinning:	Ready to use, does not require thinning.



Surface Preparation:

- Remove any dirt, oil and wood dust from the surface.
 - **New Wood Surfaces:**
 - Sand the surface with sandpaper #150/180. Thoroughly clean the generated dust.
 - **Old Uncoated Wood Surfaces:**
 - Sand the weathered surface with sandpaper #150/180. Thoroughly clean the generated dust.
 - **Coated Wood Surfaces:**
 - Do not apply the product directly on pre-coated surfaces.
 - Remove the old paint/varnish from the surface completely with a sanding machine. Thoroughly clean the generated dust.

Application:

- The product is ready to use and does not require thinning.
- Stir the product thoroughly before use and check its homogeneity. Repeat this process during the application.
- Apply the product in one coat by brush, cloth, roller, or dipping and wait 4-6 hours for complete dry.
- If a second coat is to be applied on wood with high absorbency, apply the second coat after 4-6 hours and remove the excess oil with a cloth or brush.
- Apply in the direction of the wood to get a homogeneous look.

Maintenance (when the exact product had been used before):

- Do not apply the product directly on pre-coated surfaces.
- Remove the old stain/varnish from the surface completely with sandpaper.
- Thoroughly clean the generated dust.
- Repeat the same process as described in "Application".
- Inspect annually and maintain as required.

Instructions:

- When the air temperature is high, as the wooden surface will heat up, the product may dry quickly on the surface during application and brush marking problems may occur. For this reason, Do not apply the product under direct sunlight or rain.
- Keep product closed when not in use.
- The general application temperature of the product is between 15°C to 25°C at a relative humidity range of 40-65%.
- The moisture content of the wood should max 20%.
- Do not apply linseed oil, basecoat/primer, yacht varnish before or after Prime Hybrid Oil coated surfaces.
- To provide long-life protection against decay, apply Prime Wood Preserver on untreated softwoods and wait 24 hours before applying Prime Hybrid Oil.
- The product should be protected from freezing and stored between 5°C to 35°C.
- After application, painting tools should be cleaned with soap and plenty of warm water.

**Safety Precautions:**

- USE WITH ADEQUATE VENTILATION.
- KEEP OUT OF REACH OF CHILDREN
- Do not transfer contents to other containers for storage
- Do not use empty cans for other purposes.
- To avoid overexposure, open windows, and doors or use other means to ensure fresh air entry during application and drying.
- Avoid contact with eyes and skin. Wash hands after using.
- FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists.
- If swallowed, immediately call Poison Control Center, hospital emergency room, or physician.
- Dispose of contents/cans per national regulations.
- Please refer to the product's Safety Data Sheet (SDS) for health and safety information.

Certificates:

- EN71-3 Toy Safety Certificate