



Solvent-based classic wood stain

Description: Solvent-based classic wood stain

Color: Light Oak, Burma, Walnut, Chestnut, Dark Walnut, Dark Oak, Clear, Teak, Green

Gloss: Gloosy

Type: Solvent-based

General Features:

- Silky glossy finish
- Reduces moisture uptake
- Minimizes crack formation
- Water repellent
- Resistant to UV and exterior weather conditions
- Transparent (*) and nine semi-transparent color options
- Ready to use

Packaging Size: 0,750 L., 2,5 L., 15 L.

Where To Use:

- Suitable for all exterior wood except floors
- Doors and window joinery
- Shutters
- Claddings
- Fences
- Pergolas
- Balcony railings
- Roof fringes

Product Data:

| | |
|---|---|
| Solid Content (% weight): | 39,3 ± 1 |
| Viscosity (DIN4, 20°C): | 24" ± 2 |
| Density (g/cm ³): | 0,89 ± 0,02 |
| VOC (g/L): | 536 |
| Application Method: | Brush or cloth |
| Shelf Life (5-35°C): | Two years for an unopened can |
| Number of Coats: | Two coats |
| Coverage (m ² /L): | 15-20 m ² with one coats depending on the wood type |
| Drying Time (at 20°C and 40-65% relative humidity): | Recoat: 6-8 hours Complete Dry: 12 hours |
| Thinning: | Ready to use, does not require thinning. (In scorching weather, it can be diluted with thinner by 5%.) |



Surface Preparation:

- Remove any dirt, oil, and wood dust from the surface.
 - **New Wood Surfaces:**
 - Sand the surface with sandpaper #80/120.
 - Thoroughly clean the generated dust.
 - **Old Uncoated Wood Surfaces:**
 - Sand the weathered surface with sandpaper #80/120.
 - Thoroughly clean the generated dust.
 - **Coated Wood Surfaces:**
 - Do not apply the product directly on pre-coated surfaces.
 - Remove the old paint/varnish from the surface completely with sandpaper.
 - Thoroughly clean the generated dust.

Application:

- The product is ready to use and does not require thinning. (In scorching weather, it can be diluted with thinner up to 5% maximum).
- Stir the product thoroughly before use and check its homogeneity. Repeat this process during the application.
- Apply the product in 2 coats by brush and wait 6-8 hours between coats.
- Perform a slight sanding with sandpaper #180/220 between coats.
- Apply 1 or 2 coats of the product with a cloth for coloring, depending on your preference. Applying a top coat to the product is recommended for long-term protection and a decorative appearance.
- Wait 12 hours for complete drying.
- Apply in the direction of the wood grain to get a homogeneous look.

Maintenance (when the exact product had been used before):

- Do not apply the product directly on pre-coated surfaces.
- Clean the wood surface entirely from dirt and oil and perform a slight sanding.
- Thoroughly clean the generated dust.
- Repeat the process described in "Application" with 1 or 2 coats depending on weathering.
- Inspect annually and maintain as required.

Instructions:

- FOR INTERIOR AND EXTERIOR USE.
- NOT SUITABLE FOR FLOORINGS.
- Keep product closed when not in use.
- The general application temperature of the product is between 15oC to 25oC at a relative humidity range of 40-65%.
- The moisture content of the wood should be max. 20%.
- Do not apply the product under direct sunlight or rain.
- Do not apply linseed oil, basecoat/primer, or yacht varnish before or after the product applied surfaces.
- To provide extended lifetime protection against decay, apply Prime Wood Preserver on untreated softwoods and wait 24 hours before applying the product.
- Since the clear color option does not contain pigment, it is not resistant to sunlight (UV). It is recommended to use Clear on Prime Decorative Wood Colorant as a topcoat for exterior uses.
- The product should be stored at temperatures between 5°C to 35°C.
- Painting tools should be cleaned with mineral spirits after the application.



Safety Precautions:

- USE WITH ADEQUATE VENTILATION.
- KEEP OUT OF REACH OF CHILDREN.
- Do not transfer contents to other containers for storage.
- Do not use empty cans for other purposes.
- To avoid overexposure, open windows, and doors or use other means to ensure fresh air entry during application and drying.
- Avoid contact with eyes and skin.
- Wash hands after using.
- FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. Call the Poison Control Center, hospital emergency room, or physician if swallowed.
- Dispose of contents/cans by national regulations.
- Please refer to the product's Safety Data Sheet (SDS) for health and safety information.